

Icon

Indoor Lighting - Industrial



TECHNICAL INFORMATION

Housing	UV-stabilized white polycarbonate
Optics	Opal polycarbonate diffuser
LED Lifetime	50.000 hours
Mounting System	Surface

OPTICAL SPECIFICATIONS

Optical	Symmetrical
Light Exit Angle	120°
UGR Value	80

ELECTRICAL



Power (W)	15-25W
Power Factor	>95
Light Source	SMD Mid Power LED
Cabling	Halogen-Free
Input Voltage	220-240V / 50-60 Hz

OPTIONAL

DALI
1-10V DIM
Emergency Lighting Unit

MOUNTING

Mounting Type Surface



Order Code	W	Light Source	Lm	CCT	L (mm)	Kg
06152.34.30.013	13	LED Module	1403	3000	325x100	1,3
06152.34.40.017	13	LED Module	1516	4000	325x100	1,3
06152.34.30.018	18	LED Module	1944	3000	325x100	1,3
06152.34.40.019	18	LED Module	2100	4000	325x100	1,3

All electrical values given are nominal values. The luminous flux and the associated electrical load are subject to an initial tolerance of +/- 10%. Color temperature tolerance: +/-150 K. Unless otherwise stated, values are valid for an ambient temperature of 25°C.

The information containing technical parameters and product codes in the catalog and on the website may differ from standard products due to customizations made according to projects.

Ikizler Aydınlatma has the right to make changes to the products without notice. You can get up-to-date information about the products on our website.

Phone: +90 (216) 397 22 16
Fax: +90 (216) 397 19 19
E-Mail: info@ikizleraydinlatma.com

Please visit our website for our updated information. www.ikizleraydinlatma.com

