

Dragon

Indoor Lighting - Downlights & Spotlights



TECHNICAL INFORMATION

Housing	Die-cast aluminum
Optics	Aluminium reflector & transparent diffuser
LED Lifetime	50.000 hours
Mounting System	Recessed

OPTICAL SPECIFICATIONS

Optical	Adjustable - 90° vertical, 350° horizontal
Light Exit Angle	24°
UGR Value	80

ELECTRICAL



Power (W)	30W
Power Factor	>95
Light Source	COB LED
Cabling	Halogen-Free
Input Voltage	220-240V / 50-60 Hz

OPTIONAL

DALI
Emergency Lighting Unit

MOUNTING

Mounting Type Recessed



Order Code	W	Light Source	Lm	CCT	Angle (°)	Cut-out (mm)	L (mm)	H (mm)
05310.16.30.032	30	COB LED	3200	3000	24°	175	190x160	160
05310.16.40.034	30	COB LED	3400	4000	24°	175	190x160	160



All electrical values given are nominal values. The luminous flux and the associated electrical load are subject to an initial tolerance of +/- 10%. Color temperature tolerance: +/-150 K. Unless otherwise stated, values are valid for an ambient temperature of 25°C.
The information containing technical parameters and product codes in the catalog and on the website may differ from standard products due to customizations made according to projects.
Ikizler Aydınlatma has the right to make changes to the products without notice. You can get up-to-date information about the products on our website.