

Snow-015

Indoor Lighting - Downlights & Spotlights



TECHNICAL INFORMATION

Housing	Die-cast aluminium
Optics	UV-stabilized opal diffuser
LED Lifetime	50.000 hours
L70B50	
Mounting System	Recessed

OPTICAL SPECIFICATIONS

Optical	Symmetrical
Light Exit Angle	120°
UGR Value	80

ELECTRICAL


Power (W)	10W
Power Factor	>95
Light Source	SMD Mid Power LED
Input Voltage	220-240V / 50-60 Hz

OPTIONAL

DALI
Emergency Lighting Unit
1-10V DIM
Tunable White

MOUNTING

Mounting Type	Recessed
----------------------	----------



Order Code	W	Light Source	Lm	CCT	L (mm)	Cut-out (mm)	Kg
05397.15.30.010	10	LED Module	1000	3000	147x60	130	0,9
05397.15.40.010	10	LED Module	1150	4000	147x60	130	0,9

All electrical values given are nominal values. The luminous flux and the associated electrical load are subject to an initial tolerance of +/- 10%. Color temperature tolerance: +/-150 K. Unless otherwise stated, values are valid for an ambient temperature of 25°C.
The information containing technical parameters and product codes in the catalog and on the website may differ from standard products due to customizations made according to projects.
Ikizler Aydınlatma has the right to make changes to the products without notice. You can get up-to-date information about the products on our website.

Phone: +90 (216) 397 22 16
Fax: +90 (216) 397 19 19
E-Mail: info@ikizleraydinlatma.com

Please visit our website for our updated information. www.ikizleraydinlatma.com

