

Silverpit

Indoor Lighting - Downlights & Spotlights



TECHNICAL INFORMATION

Housing	Aluminum
Optics	Matte silver reflector with glare control
Diffuser	Semi-frosted polycarbonate
LED Lifetime	50.000 hours
Mounting System	Recessed
Size Options	92-118-141 mm.

OPTICAL SPECIFICATIONS

Optical	Symmetrical
Light Exit Angle	45°
UGR Value	80

ELECTRICAL


Power Factor	>95
Light Source	COB LED
Cabling	Halogen-Free
Input Voltage	220-240V / 50-60 Hz

OPTIONAL

DALI
1-10V DIM
Emergency Lighting Unit

MOUNTING

Mounting Type	Recessed
----------------------	----------



Order Code	W	Light Source	Lm	CCT	Angle (°)	L (mm)	Cut-out (mm)	K
05113.14.30.022	19	COB LED	1900	3000	45°	141x120	130	0
05113.14.40.023	19	COB LED	2100	4000	45°	141x120	130	0
05113.11.30.014	14	COB LED	1400	3000	45°	118x102	105	0
05113.11.40.015	14	COB LED	1520	4000	45°	118x102	105	0
05113.09.30.010	10	COB LED	1000	3000	45°	92x95	82	0
05113.09.40.011	10	COB LED	1120	4000	45°	92x95	82	0
05113.14.30.029	30	COB LED	3200	3000	45°	141x120	130	0
05113.14.40.029	30	COB LED	3520	4000	45°	141x120	130	0



All electrical values given are nominal values. The luminous flux and the associated electrical load are subject to an initial tolerance of +/- 10%. Color temperature tolerance: +/-150 K. Unless otherwise stated, values are valid for an ambient temperature of 25°C.
The information containing technical parameters and product codes in the catalog and on the website may differ from standard products due to customizations made according to projects.
Ikizler Aydınlatma has the right to make changes to the products without notice. You can get up-to-date information about the products on our website.