

# Corvus-G 900

Indoor Lighting - Recessed



## TECHNICAL INFORMATION

<b>Housing</b>	Extruded aluminum profile housing
<b>Optics</b>	UV-stabilized opal diffuser
<b>LED Lifetime</b>	50.000 hours
<b>Mounting System</b>	Recessed

## OPTICAL SPECIFICATIONS

<b>Optical</b>	Symmetrical
<b>Light Exit Angle</b>	120°
<b>UGR Value</b>	80

## ELECTRICAL



<b>Power (W)</b>	69W
<b>Power Factor</b>	>95
<b>Light Source</b>	SMD Mid Power LED
<b>Cabling</b>	Halogen-Free
<b>Input Voltage</b>	220-240V / 50-60 Hz

## OPTIONAL

DALI  
1-10V DIM  
Emergency Lighting Unit  
Tunable White

## MOUNTING

<b>Mounting Type</b>	Recessed
----------------------	----------



Order Code	W	Light Source	Lm	CCT	L (mm)	Cut-out (mm)	Kg
02130.90.30.065	69	LED Module	6900	3000	900x82	890	5,6
02130.90.40.069	69	LED Module	6980	4000	900x82	890	5,6

All electrical values given are nominal values. The luminous flux and the associated electrical load are subject to an initial tolerance of +/- 10%. Color temperature tolerance: +/-150 K. Unless otherwise stated, values are valid for an ambient temperature of 25°C.  
The information containing technical parameters and product codes in the catalog and on the website may differ from standard products due to customizations made according to projects.  
Ikizler Aydınlatma has the right to make changes to the products without notice. You can get up-to-date information about the products on our website.

**Phone:** +90 (216) 397 22 16  
**Fax:** +90 (216) 397 19 19  
**E-Mail:** [info@ikizleraydinlatma.com](mailto:info@ikizleraydinlatma.com)

Please visit our website for our updated information. [www.ikizleraydinlatma.com](http://www.ikizleraydinlatma.com)

