


Silverline

Indoor Lighting - Recessed



Order Code	W	Light Source	Lm	CCT	WxLxH (mm)	Kg
02174.66.30.029	33	LED Module	3654	3000	595x595x25	3,9
02174.66.40.030	33	LED Module	4200	4000	595x595x25	3,9

TECHNICAL INFORMATION

Housing	Sheet steel housing
Optics	Aluminium plated PC reflector with glare control
LED Lifetime	50.000 hours
Mounting System	Recessed

OPTICAL SPECIFICATIONS

Optical	Symmetrical
Light Exit Angle	36°
UGR Value	80

ELECTRICAL

Power (W)	33W
Power Factor	>95
Light Source	SMD Mid Power LED
Cabling	Halojen-Free
Input Voltage	220-240V / 50-60 Hz

OPTIONAL

DALI
Emergency Lighting Unit

MOUNTING

All electrical values given are nominal values. The luminous flux and the associated electrical load are subject to an initial tolerance of +/- 10%. Color temperature tolerance: +/-150 K. Unless otherwise stated, values are valid for an ambient temperature of 25°C.
The information containing technical parameters and product codes in the catalog and on the website may differ from standard products due to customizations made according to projects.
Ikizler Aydınlatma has the right to make changes to the products without notice. You can get up-to-date information about the products on our website.

Phone: +90 (216) 397 22 16
Fax: +90 (216) 397 19 19
E-Mail: info@ikizleraydinlatma.com

Please visit our website for our updated information. www.ikizleraydinlatma.com

