NEST DUO-R

Standard Colours
Ral 9016 | Ral 9006 | Ral 9005

Joint Colours
Black | Red | Green

CE | IP 20 | RoHS COMPLIANT

OPTICAL
Direct&Indirect light distribution
36° beam angle
UGR<16
Lifetime (L90/ B10): 50000 h.(tq+25°C)
Lifetime (L80/B20): 100000 h. (tq+25°C)
SMD LED module
Color rendering index: CRI>80
MacAdams SDCM 3

MECHANICAL
Extruded aluminium profile housing
Dark reflector for glare control
Decorative joint part with colour options
IP20 protection degree
Impact resistance IK02
Glow-wire test resistance 650°C

ELECTRICAL
Halogen-free wiring
220-240V-50/60Hz
Power factor >0.95
Constant current, Class I, isolated driver
CE - IEC 60598-1 - EN 60598-1
Ambient temperature from -20°C to +50°C
On-Off Control - (Code: .N000)

OPTIONAL
DALI - (Code: .DXXX)
1-10V - (Code: .MXXX)
CBS connection
Color temperature (K) options
RAL colour selection

INSTALLATION
Ceiling suspended.







Product Code	Power (W)	Lumen (lm)	CCT (K)	CRI	Dimensions WxLxH (mm)	Cut-Out WxL (mm)	Weight (kg)
01190.11.30.053	51	5390	3000K	Ra>80	100x1130x190	N/A	3,2

All electrical values given are rated values. Luminous flux and connected electrical load are subject to an initial tolerance of +/- 10%. Tolerance of colour temperature: +/-150 K. Unless stated otherwise, the values apply to an ambient temperature of 25°C.
Any information including technical parameters and product codes may differ from standard products in catalogue & web site due to customization made per projects.
Ikizler Lighting has the right to make changes or cancellations on the products without notification. Updated information on the products can be received from our web site.

Phone +90 (216) 397 22 16
Fax +90 (216) 397 19 19
E-Mail info@ikizlerlighting.com

ikizler