DRAW-M



IP 65 | IK 08 | RoHS COMPLIANT

OPTICAL
Direct symmetric distribution
Beam angle 120°
UGR <22
Luminous efficacy >100 lm/W
Lifetime (L90/B10): 50000 h.(tq+25°C)
Lifetime (L80/B20): 100000 h. (tq+25°C)
SMD LED module
Color rendering index: CRI>80
MacAdams SDCM 3

MECHANICAL
Single piece extruded
polycarbonate housing
Opal polycarbonate diffuser
IP65 protection degree
Impact resistance IK08
Glow-wire test resistance 650°C

ELECTRICAL
Halogen-free wiring
220-240V-50/60Hz
Power factor >0.95
Constant current, Class I, isolated driver
CE - IEC 60598-1 - EN 60598-1
Ambient temperature from -20°C to +50°C
On-Off Control - (Code: .N000)

OPTIONAL
DALI - (Code: .DXXX)
1-10V - (Code: .MXXX)
Tunable White
Flicker-free - (Code: .FXXX)
Emergency battery - (Code .X3HT)
CBS connection
Sensor applications
Color rendering index: CRI >90
Color temperature (K) options
Suspension kit

INSTALLATION
Surface or suspended mounted.





Product Code	Power (W)	Lumen (lm)	CCT (K)	CRI	Dimensions WxLxH (mm)	Cut-Out Q (mm)	Weight (kg)
07102.11.40.044	37	4800	4000K	Ra>80	53x1144x58	N/A	1,5

All electrical values given are rated values. Luminous flux and connected electrical load are subject to an initial tolerance of +/- 10%. Tolerance of colour temperature: +/-150 K. Unless stated otherwise, the values apply to an ambient temperature of 25°C.
Any information including technical parameters and product codes may differ from standard products in catalogue & web site due to customization made per projects.
Ikizler Lighting has the right to make changes or cancellations on the products without notification. Updated information on the products can be received from our web site.

Phone +90 (216) 397 22 16
Fax +90 (216) 397 19 19
E-Mail info@ikizlerlighting.com
www.ikizlerlighting.com